PIZZA PREPARATION TABLE

Model: PA68N

Natural Refrigerant R-290 Model

68" Pizza Preparation Refrigerator with Solid Doors

Heavy gauge #300 series stainless steel top, stainless steel front and end panels, aluminum interior.



Options and Accessories

(upcharge and lead times may apply)

Stainless steel interior	Vision panel lid
Stainless steel back	Door/drawer locks
Overshelves (single or double)	Adjustable legs
Condensing unit on left (standard on right)	Front breathing
Wire rod garnish rack	Special electrical requirements (consult factory)

Drawer in lieu of half door above the condensing unit*

Drawers in lieu of doors (consult factory)**

Consult factory for other model configurations, options and accessories.

- * Drawer section above condensing unit holds (1) 12 x 20 x 6 pan.
- **Two tier (larger section): (2) 12x20x6 pans per drawer



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Project Name:		
Model Specified:		
Location:		
Item No:	Quantity:	
AIA #:	SIS #:	

Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Unique forced air design utilizes fans (approx. every 12") across the entire back of unit for even distribution of cold

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide out condensing unit

Expansion valve system

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome door handles

Spring loaded, self closing doors

Magnetic snap in Santoprene™ door gaskets

Heavy duty, epoxy coated steel shelves

19" deep, full length nylon cutting board

Insulated lids (with heavy duty hinge pins)

(8) pan top divider bars*

5" casters

* Pans supplied by others

MODEL FEATURES

Reversing condenser fan²

Ergonomically-friendly raised angle rail

Electronic control, off-cycle defrost

Refrigerated section with door above the condensing unit

Field rehingeable doors

¹ R-290 refrigerant meets all federal and state regulatory requirements.

² Fan runs in reverse for short period on startup to blow away any debris.

NOTE: Models come standard with a door above the condensing unit. A drawer above the condensing unit is an option.

APPROVAL:

Model Specifications

DIMENSIONAL DATA	
Net Capacity (cubic feet)	22 (623 cu I)
Width, Overall (inches)	68 (1727 mm)
Depth, Overall (inches) (including cutting board & bumpers)	38 ½ (972 mm)
Height, Overall (inches) (including 5" casters)	39 (989 mm)
Depth, Cutting Board (inches)	19 (483 mm)
Shelf Area (square feet)	9.8 (0.9 sq m)
Number of Shelves	2
Number of Full Doors	2
Number of Half Doors	1
Interior Depth (inches)	27 3/8 (695 mm)
Interior Height (inches)	26 (660 mm)
Interior Height (inches) (above condenser)	12 ½ (318 mm)
Interior Width (inches)	64 (1626 mm)
PAN TOP	
PAN TOP Divider Bars (supplied with model)	(8) CM1-0111
	(8) CM1-0111 (9) ½3
Divider Bars (supplied with model)	. ,
Divider Bars (supplied with model) Pan Capacity (pans supplied by others)	. ,
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA	(9) 1/3
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.)	(9) ½3 1/3+
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)*	(9) ½3 1/3+
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)* ELECTRICAL DATA	(9) ¹ / ₃ ¹ / ₃ + 4220
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)* ELECTRICAL DATA Voltage (International)	(9) ¹ / ₃ ¹ / ₃₊ 4220 115/60/1 (220/50/1)
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)* ELECTRICAL DATA Voltage (International) Total Amps (International) 10 ft. Cord/Plug [attached]	(9) ½3 ½3+ 4220 115/60/1 (220/50/1) 7.4 (5.3) Yes
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)* ELECTRICAL DATA Voltage (International) Total Amps (International) 10 ft. Cord/Plug [attached] (International)	(9) ½3 ½3+ 4220 115/60/1 (220/50/1) 7.4 (5.3) Yes
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)* ELECTRICAL DATA Voltage (International) Total Amps (International) 10 ft. Cord/Plug [attached] (International) SHIPPING DATA	(9) ½3 ½3+ 4220 115/60/1 (220/50/1) 7.4 (5.3) Yes (No)
Divider Bars (supplied with model) Pan Capacity (pans supplied by others) REFRIGERANT DATA Condensing Unit Size (H.P.) Capacity (BTU per hour)* ELECTRICAL DATA Voltage (International) Total Amps (International) 10 ft. Cord/Plug [attached] (International) SHIPPING DATA Weight (pounds)	(9) ¹ / ₃ ¹ / ₃₊ 4220 115/60/1 (220/50/1) 7.4 (5.3) Yes (No) 488 (221 kg)

 * Rating @ +25°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

Continental® Refrigerator

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





IMPORTANT NOTE: If the cabinet is located directly against a wall, a <u>minimum clearance of 3" is required on sides</u>, front and rear.